

广州中逸光电子科技有限公司

测试报告 (Inspection report)

产品型号: MF60-S12				批号:		日期: 2016-4-7		仪器编号: ADS1062C, LW2676												
1. 耐压测试																				
Input to Output 4000 VAC Leakage current 0.83 mA at 1 min OK!																				
2. 测试数据																				
输入				输出			效率	纹波噪声 (mV)	电压精度	电压调整率	负载调整率									
U _{in} (VAc)		I _{in} (A)	P _{in}	U _{out} (V)	I _{out} (A)	P _{out}														
85	最小载	0.147	7.14	12.240	0.500	6.120	85.71%	36	1.91%	0.16%	0.09%									
	半载	0.619	35.50	12.230	2.500	30.575	86.13%	40												
	满载	1.321	73.70	12.210	5.000	61.050	82.84%	60												
115	最小载	0.180	7.16	12.240	0.500	6.120	85.47%	36				1.91%	0.16%	0.09%						
	半载	0.479	35.20	12.230	2.500	30.575	86.86%	36												
	满载	0.927	71.00	12.210	5.000	61.050	85.99%	44												
230	最小载	0.201	7.46	12.240	0.500	6.120	82.04%	36							1.91%	0.16%	0.09%			
	半载	0.625	35.40	12.230	2.500	30.575	86.37%	64												
	满载	1.033	70.48	12.229	5.000	61.145	86.76%	36												
264	最小载	0.265	7.60	12.240	0.500	6.120	80.53%	36										1.91%	0.16%	0.09%
	半载	0.986	35.60	12.230	2.500	30.575	85.88%	64												
	满载	1.654	70.50	12.210	5.000	61.050	86.60%	36												
									测试结果	符合技术手册参数要求 pass										
3. 稳定性																				
Vout	100%-0%-100%load			启动模式		turn on		测试结果	符合技术手册参数要求 pass											

测试	姚桂花	2016-4-7	审核	谢洪发	2016-4-7	批准	罗胜东	2016-4-7
----	-----	----------	----	-----	----------	----	-----	----------