

广州中逸光电子科技有限公司

测试报告 (Inspection report)

产品型号: MF60-S18			批号:		日期: 2016-4-19		仪器编号: LW2676;ADS1062C				
1. 耐压测试											
Input to Output 4000 VAC Leakage current 0.78 mA at 1 min OK!											
2. 测试数据											
输入				输出							
U _{in} (VAc)		I _{in} (A)	P _{in}	U _{out} (V)	I _{out} (A)	P _{out}	效率	纹波噪声 (mV)	电压精度	电压调整率	负载调整率
100	最小载	0.127	6.82	18.22	0.33	6.01	88.16%	20	1.11%	0.00%	0.055%
	半载	0.521	33.80	18.22	1.67	30.43	90.02%	20			
	满载	1.036	68.80	18.20	3.33	60.61	88.09%	50			
140	最小载	0.770	6.91	18.21	0.33	6.01	86.97%	20			
	半载	0.104	33.80	18.21	1.67	30.41	89.97%	20			
	满载	0.401	68.10	18.20	3.33	60.61	89.00%	40			
240	最小载	0.089	7.39	18.21	0.33	6.01	81.32%	20			
	半载	0.294	34.60	18.21	1.67	30.41	87.89%	50			
	满载	0.521	68.10	18.20	3.33	60.61	89.00%	30			
									测试结果	符合技术手册参数要求 pass	
3. 稳定性											
Vout	100%-0%-100%load				启动模式	turn on			测试结果	符合技术手册参数要求 pass	

测试	姚桂花2016-4-19	审核	谢洪发 2016-4-19	批准	罗胜东 2016-4-19
----	--------------	----	---------------	----	---------------