

广州中逸光电子科技有限公司

测试报告 (Inspection report)

产品型号: MF60-S24			批号:			日期: 2016-6-8			仪器编号: LW2676;ADS1062C		
1. 耐压测试											
Input to Output 4000 VAC Leakage current 0.80 mA at 1 min OK!											
2. 测试数据											
输入				输出							
U _{in} (VAc)		I _{in} (A)	P _{in}	U _{out} (V)	I _{out} (A)	P _{out}	效率	纹波噪声 (mV)	电压精度	电压调整率	负载调整率
100	最小载	0.127	6.76	23.970	0.250	5.993	88.65%	20	-0.33%	0.04%	0.21%
	半载	0.521	33.30	23.960	1.250	29.950	89.94%	20			
	满载	1.036	66.70	23.920	2.500	59.800	89.66%	20			
140	最小载	0.770	6.68	23.980	0.250	5.995	89.75%	30			
	半载	0.104	33.45	23.950	1.250	29.938	89.50%	20			
	满载	0.401	66.70	23.930	2.500	59.825	89.69%	20			
240	最小载	0.089	6.66	23.970	0.250	5.993	89.98%	25			
	半载	0.294	33.33	23.950	1.250	29.938	89.82%	20			
	满载	0.521	66.80	23.920	2.500	59.800	89.52%	20			
									测试结果	符合技术手册参数要求 pass	
3. 稳定性											
Vout	100%-0%-100%load				启动模式	turn on			测试结果	符合技术手册参数要求 pass	

测试	姚桂花2016-6-8	审核	谢洪发 2016-6-8	批准	罗胜东 2016-6-8
----	-------------	----	--------------	----	--------------